



SM0014
Speed-Midget 4-ton Extra Short Ram

| <u>Specifications</u> | <u>Inch</u> | <u>Metric</u> |
|--|-----------------------|--------------------|
| Effective Piston Area | 1.107 in ² | 7 cm ² |
| Piston Travel/Stroke - in | .158" | 4 mm |
| Maximum Capacity (1 st stage) | 4 tons | 3.6 _t |
| Maximum Capacity (2 nd stage) | N/A | |
| Retracted Height | 2-5/16" | 59 mm |
| Piston Travel | 1" | 25 mm |
| Extended Height | 3-5/16" | 84 mm |
| Extended Height (1 st stage) | N/A | |
| Extended Height (2 nd stage) | N/A | |
| Stroke | 1" | 25 mm |
| Cylinder Bore Diameter | 1-3/16" | 30 mm |
| Piston Diameter (outer) | 1-1/16" | 27 mm |
| Piston Diameter (inner) | N/A | |
| Spring Return | N/A | |
| Hose Hole Thread | 1/4" - 18 NPTF | |
| Maximum O.D. | 2" | 51 mm |
| Accessory Attachment Method, Ram End | N/A | |
| Body Male Thread | N/A | |
| Accessory Attachment Method, Base End | N/A | |
| Weight | 1-1/2 lbs | .7 kg |
| Oil Capacity | 1.05 in ³ | 18 cm ³ |
| Repair Kit Numbers | RSM024A & RSM024AP | |