



SM0014T

Two-Stage 4-ton Telescoping Mini-Ram

<u>Specifications</u>	<u>Inch</u>	<u>Metric</u>
Effective Piston Area	1.107 in ²	7 cm ²
Piston Travel/Stroke - in	.158"	4 mm
Maximum Capacity (1 st stage)	4 tons	3.6 _t
Maximum Capacity (2 nd stage)	1 ton	.9 _t
Retracted Height	2-5/16"	59 mm
Piston Travel	2"	51 mm
Extended Height	4-5/16"	109 mm
Extended Height (1 st stage)	3-5/16"	84 mm
Extended Height (2 nd stage)	4-5/16"	109 mm
Stroke	2"	51 mm
Cylinder Bore Diameter	1-3/16"	30 mm
Piston Diameter (outer)	1-1/16"	27 mm
Piston Diameter (inner)	5/8"	16 mm
Spring Return	N/A	
Hose Hole Thread	1/4" - 18 NPTF	
Maximum O.D.	2"	51 mm
Accessory Attachment Method, Ram End	N/A	
Body Male Thread	N/A	
Accessory Attachment Method, Base End	N/A	
Weight	1-1/2 lbs	.7 kg
Oil Capacity	1.35 in ³	22 cm ³
Repair Kit Numbers	RSM0014T & RSM0014TP	