



SM0034P
2-1/2 - ton Pull Ram

<u>Specifications</u>	<u>Inch</u>	<u>Metric</u>
Effective Piston Area	1.227 in ²	8 cm ²
Piston Travel/Stroke - in	.175"	4 mm
Maximum Capacity (1 st stage)	2-1/2 tons	2.2 _t
Maximum Capacity (2 nd stage)	N/A	
Retracted Height	11-11/16""	297 mm
Piston Travel	5"	127 mm
Extended Height	16-11/16"	424 mm
Extended Height (1 st stage)	N/A	
Extended Height (2 nd stage)	N/A	
Stroke	5"	127 mm
Cylinder Bore Diameter	1-1/4"	32 mm
Piston Diameter (outer)	3/4"	19 mm
Piston Diameter (inner)	N/A	
Spring Return	YES	
Hose Hole Thread	1/4" - 18 NPTF	
Maximum O.D.	2-3/4"	70 mm
Accessory Attachment Method, Ram End	Clevis Pin	
Body Male Thread	1-1/2" - 12 UN	
Accessory Attachment Method, Base End	Clevis Pin	
Weight	4-3/8 lbs	2 kg
Oil Capacity	5.38 in ³	88 cm ³
Repair Kit Numbers	RSM0034P & RSM0034PP	

SM0034P-CC = above supplied with two (2) CA0166, single chain catch
 SM0034P-GG = above supplied with two (2) CA0177, clevis grab hook
 SM0034P-SS = above supplied with two (2) CA0176, clevis slip hook